

**Material Safety Data Sheet**  
Supplied By

Graftobian Theatrical  
510 Tasman Street  
Madison, WI 53714  
608-222-7848  
Fax:608-222-7893

1. Product Identification:

Product: PRO ADHESIVE

2. Ingredients: Acrylic Polymer , Individual Residual Monomers , Aqua Ammonia , Water.

Flammable Liquid: NO

3. Health Effect Information:

Eye Contact: This product Can cause slight irritation.

Skin Contact: No Evidence of harmful effects..

Ingestion: If swallowed, give 2 glasses of water to drink. Consult a physician.

4. Fire Protection:

Flash Point: noncombustible

Auto Ignition Temp: 700 Degrees F.

Unusual fire and Explosive Conditions: Dense smoke may be generated while burning.  
Carbon dioxide , Carbon Monoxide and other Oxides may be generated as products of combustion

5. Physical Properties:

Boiling Point: 212 deg. F.

Melting Point: n/a

Appearance: Milky white liquid

Odor: paint like odor

Vapor Pressure: 17 mm Hg @ 20deg. C/68 deg. F

(2)  
**PRO ADHESIVE**

Solubility: soluble in water

Molecular Weight: Varies

6. Personal Health Protection:

Eye Contact: Eye protection is not required under normal use. If material is handled such that it could be splashed into eyes, wear a plastic face shield or safety goggles.

Skin Protection: None required

Respiratory Protection: None normally required

7. Emergence and first aid Information:

Eye Contact: Flush eyes immediately with plenty of water for at least 15 minutes. Consult a physician if irritation persists.

Inhalation: Remove to fresh air .

Ingestion: If ingestion occurs , give 2 glasses of water to drink. Consult a physician.

8. Environmental precautions:

In case of spill or release: Mop or wipe up before drying with paper towels and place in proper waste container.

9. Waste Disposal.

All disposables must comply with local, state and Federal regulations.